

APECS DOORS



MADE
IN RUSSIA

SL-ID-80, 80M series



EVEN BETTER NOISE PROTECTION

Noise isolation of door 35 dB, which is 30% better than the two-dimensional glass. The thickness of the noise absorbing door panels increased to 12 mm.

EVEN BETTER TIGHTNESS

The overlay on the level lock with the patented automatic shutter does not pass noise and a smell. German door sealing system, 2 circuits.

CHOOSE YOUR DESIGN

Combine the patterns and colors of your door as you like. We do not limit your choice of design.

OUTWARD OPENING OF THE DOOR

We offer the standard. European opening option.

APECS DOORS



MADE
IN RUSSIA

TECHNICAL CHARACTERISTICS

	SL-ID-80	SL-ID-80M
Design features	2 seal contours Metal 1,2 mm Door leaf thickness - 75 mm Door frame - 110 mm Schlegel seal	2 seal contours Metal 1,2 mm Door leaf thickness - 75 mm Door frame - 110 mm Schlegel seal
Painting	Polymer coating	Polymer coating
Finish outside	Metal	MDF 12 mm, milling, PVC film
Finish inside	MDF 12 mm, milling, PVC film	MDF 12 mm, milling, PVC film
Heater	Door leaf - mineral wool "KNAUF" Door frame "KNAUF"	Door leaf - mineral wool "KNAUF" Door frame "KNAUF"
Locks and fittings	Mettem lock Protector Basic Handle APECS 04 series Doorviewer Apecs 50/90	Mettem lock Protector Basic Handle APECS 04 series Doorviewer Apecs 50/90